

EVALUATION OF THE CONFORMITY

2020TM0207UE

APPLICATION DATE

27/02/2020

APPLICANT

BOSS M MODA KONF ÜRÜNLERİ SANAYİ TİC LTD ŞTİ
MİMAR SİNAN MAH. ANKARA YOLU BULVARI NO:191
TR-19100 ÇORUM

Att. İbrahim Çetintürk

IDENTIFICATION AND DESCRIPTION OF SAMPLES

REFERENCES

DZ COVERALL

TESTS CARRIED OUT

- OBSERVATIONS
- DESCRIPTION OF SAMPLE
- ESSENTIAL REQUIREMENTS
- EVALUATION FOR EU TYPE CERTIFICATION
- CONCLUSION OF THE CONFORMITY EVALUATION

Rev.1 This revision cancels and replaces the previous
Error in applicant data

1 / 26



OBSERVATIONS

PPE TYPE COVERALL referenced DZ COVERALL presented for the “EU” Type certification to comply with the Regulation (EU) 2016/425, based on the standards EN ISO 13688:2013, EN 13034: 2005+A1: 2009, EN 14126:2003/AC:2004 and EN ISO 13982-1:2004/A1:2010.

The manufacturer has presented the applicable technical documentation according to Annex III of the Regulation (UE) 2016/425.

The customer has presented the following samples:

- Twenty (20) complete garment from the DZ COVERALL

With compliance to the Regulation (EU) 2016/425.

>>>



LIST OF MATERIALS

DZ COVERALL

The PPE is made in the following materials according to technical documentation presented by the client:

- White non-woven fabric composition – 60% polyethylene and 40% polypropylene (3,6% Spunbond Hydrophobic Hotmelt) with an approximate weight of 55 g/m².
- Double-sided adhesive tape (central closure)
- Elastic tape (hood, cuffs, pants bottom)

The PPE is available in the following sizes:

SIZE	Total height of wearer (cm)	Chest measurement (cm)
S	162-170	95-105
M	168-176	105-115
L	174-182	115-121
XL	180-180	121-129

_____///



DESCRIPTION OF SAMPLES

DZ COVERALL

Coverall made in non-woven fabric with an exterior white laminated.





ESSENTIAL HEALTH AND SAFETY REQUIREMENTS

Annex II Regulation (EU) 2016/425	Clauses of Standard EN ISO 13688:2013
1.2.1. Absence of inherent risks and other nuisance factors	5.3
1.2.1.1. constituent materials	4.2
1.2.1.2. Satisfactory surface condition of all PPE parts in contact with the user	4.4
1.4. Instrucciones e información del fabricante / Manufacturer's instructions and information	8
2.12. PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	6,7

Annex II Regulation (EU) 2016/425	Clauses of Standard EN 14126:2003/AC:2004
1.1.2.2. Classes of protection appropriate to different levels of risk	4.1.4
1.3.1. Adaptation of PPE to user morphology	4.3
1.3.2 Lightness and strength	4.1.2, 4.2
1.4. Manufacturer's instructions and information	6
2.12 PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	5
3.10. Protection against substances and mixtures which are hazardous to health and against harmful biological agents	4.3, 4.1.4

///



ESSENTIAL HEALTH AND SAFETY REQUIREMENTS

Annex II Regulation (EU) 2016/425	Clauses of Standard EN 13034:2005 + A1:2009
1.2.1 Absence of inherent risks and other nuisance factors	4.1
1.2.1.1 Suitable constituent materials	4.1
1.3.2 Lightness and strength	4.1
3.10.2 Protection against cutaneous and ocular contact	4.1
3.10.2 Protection against cutaneous and ocular contact	4.2.1
1.3.2 Lightness and strength	4.2.2
1.2.1.3 Maximum permissible user impediment	5.1
2.4 PPE subject to ageing	5.1
3.10.2 Protection against cutaneous and ocular contact	5.1
1.1.1 Ergonomics	5.2
1.2.1.3 Maximum permissible user impediment	5.2
3.10.2 Protection against cutaneous and ocular contact	5.2
2.12 PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	6
1.3.3 Compatibility of different types of PPE intended for simultaneous use	7
2.4 PPE subject to ageing	7
2.12 PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	7

///



ESSENTIAL HEALTH AND SAFETY REQUIREMENTS

Annex II Regulation (EU) 2016/425	Clauses of Standard EN ISO 13982-1: 2004/A1:2010
1.2.1.1. Suitable constituent materials	4.1
1.3.2. Lightness and strength	4.1
1.3.2. Lightness and strength	4.2
3.10.2. Protection against cutaneous and ocular contact	4.2.1
1.3.1. Adaptation of PPE to user morphology	4.3
1.3.3. Compatibility of different types of PPE intended for simultaneous use	4.3
1.1.2.1. Optimum level of protection	4.3.1
1.2.1.2. Satisfactory surface condition of all PPE parts in contact with the user	4.3.1
Ergonomics	4.3.2
1.1.2.1. Optimum level of protection	4.3.2
1.2.1.3. Maximum permissible user impediment	4.3.2
3.10.2. Protection against cutaneous and ocular contact	4.3.2
1.4 Manufacturer's instructions and information	5
2.12. PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	5
1.3.3. Compatibility of different types of PPE intended for simultaneous use	6
1.4. Manufacturer's instructions and information	6
2.12. PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	6

///



EVALUATION

The following points of the PPE TYPE COVERALL referenced DZ COVERALL, according to Regulation (EU) 2016/425 and the technical specifications applicable to it, according to the harmonized standard EN ISO 13688:2013, EN 13034:2005 + A1:2009, EN 14126:2003/AC:2004 and EN ISO13982-1:2004/A1:2010.

1.- TECHNICAL DOCUMENTATION AND MARKING

	RELATED DOCUMENT	CLAUSE	RESULTS
Technical documentation.	Regulation (UE) 2016/425	Annex III	Achieved
Marking	EN ISO 13688:2013	7	Achieved
	EN 13034:2005 + A1:2009	6	
	EN 14126:2003/AC:2004	5	
	EN-ISO 13982-1:2004/A1:2010	5	
Manufacturer information (1)	Regulation (UE) 2016/425	Annex II point 1.4	Achieved
	EN ISO 13688:2013	8	Achieved
	EN 13034:2005 + A1:2009	7	
	EN 14126:2003/AC:2004	6	
	EN-ISO 13982-1:2004/A1:2010	6	

⁽¹⁾ It has been verified about the version in English presented by the client.

»»»



EVALUATION

2.- REQUIREMENTS

2.1.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN ISO 13688:2013

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Ergonomics	4	The garment fulfills ergonomics requirement	Achieved	2020TM0206
Innocuousness	4.2.a)	Chromium (VI) content in leather clothing shall not exceed 3 mg/kg	Not applicable	---
	4.2.b)	All metallic materials which could come into prolonged contact with the skin shall have a release of nickel of less than 0,5 µg/cm per week	Not tested	---
	4.2.c)	Protective clothing material shall have a pH value greater than 3,5 and less than 9,5	fabric Achieved	19.0.84437
	4.2.d)	Forbidden azoic colorants shall not be detectable	Not applicable	---
Design	4.3	The garment fulfills design requirement	Achieved	2020TM0206

----->>>



EVALUATION

2.1.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN ISO 13688:2013

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Estabilidad dimensional, tras 5 ciclos a 60°C Dimensional stability	5.3	Changes of dimension due to cleaning shall not exceed 3% for woven materials and 5% for knitted material and nonwovens.	Not applicable	---
Sizing	6	Protective clothing shall be marked with its size based on body dimensions measured in centimetres.	Achieved	2020TM0206

—————>>>



EVALUATION

2.2.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 14126:2003/AC:2004

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Resistance to abrasión	4.1.2	According to the point 4.4 of the Standard EN 14325: 2018 Class 1 10 < cycles < 40 Class 2 40 < cycles < 100 Class 3 100 < cycles < 400 Class 4 400 < cycles < 1000 Class 5 1000 < cycles < 2000 Class 6 > 2000 cycles	Achieved Class 4	2020TM1850
Compression-folding flex cracking	4.1.2	According to the point 4.5 of the Standard EN 14325: 2018 Class 1 500 < cycles < 1250 Class 2 1250 < cycles < 3000 Class 3 3000 < cycles < 8000 Class 4 8000 < cycles < 20000 Class 5 20000 < cycles < 50000 Class 6 > 50000 cycles	Achieved Class 6	2020TM0206

—————>>>



EVALUATION

2.2.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 14126:2003/AC:2004

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Compression-folding flex cracking at -30°C	4.1.2	According to the point 4.6 of the Standard EN 14325: 2018 Class 1 100 < cycles < 200 Class 2 200 < cycles < 500 Class 3 500 < cycles < 1000 Class 4 1000 < cycles < 2000 Class 5 2000 < cycles < 4000 Class 6 > 4000 cycles	Achieved Class 6	2020TM06
Determination of tear resistance	4.1.2	According to the point 4.7 of the Standard EN 14325: 2018 Class 1 10 < N < 20 Class 2 20 < N < 40 Class 3 40 < N < 60 Class 4 60 < N < 100 Class 5 100 < N < 150 Class 6 > 150 N	Achieved Class 1	2020TM1850

—————>>>



EVALUATION

2.2.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 14126:2003/AC:2004

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Tensile	4.1.2	According to the point 4.9 of the Standard EN 14325: 2018 Class 1 $30 < N < 60$ Class 2 $60 < N < 100$ Class 3 $100 < N < 250$ Class 4 $250 < N < 500$ Class 5 $500 < N < 1000$ Class 6 $> 1000 N$	Achieved Class 2	2020TM0206
Puncture resistance	4.1.2	According to the point 4.10 of the Standard EN 14325: 2018 Class 1 $5 < N < 10$ Class 2 $10 < N < 50$ Class 3 $50 < N < 100$ Class 4 $100 < N < 150$ Class 5 $150 < N < 250$ Class 6 $> 250 N$	Achieved Class 2	2020TM1850
Resistance to ignition	4.1.2	According to the point 4.14 of the Standard EN 14325: 2018 material shall not form droplets and it shall not continue to burn for more than 5 s after removal from the flame	Not Achieved	2020TM0206

—————>>>



EVALUATION

2.2.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 14126:2003/AC:2004

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Resistance to flame	4.1.2	According to the point 4.15 of the Standard EN 14325: 2018 material shall not form droplets and it shall not continue to burn for more than 5 s after removal from the flame Class 1 Specimen stops for 5 s in the flame Class 2 Specimen stops for 1 s in the flame Class 3 Specimen passes through the flame without stopping	Not Tested	---
Resistance to permeation by chemicals	4.1.3	According to the point 4.11 of the Standard EN 14325: 2018 Class 1 10 < min < 30 Class 2 30 < min < 60 Class 3 60 < min < 120 Class 4 120 < min < 240 Class 5 240 < min < 480 Class 6 > 480 min	Not tested	---

>>>



EVALUATION

2.2.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 14126:2003/AC:2004

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Repellency to liquids	4.1.3	According to the point 4.12 of the Standard EN 14325: 2018 Class 1 > 70% Class 2 > 80% Class 3 > 90%	Sulphuric Acid 30% Sodium Hydroxide 10% O-Xylene 1-butanol Achieved	2020TM0206
Resistance to penetration to liquids	4.1.3	According to the point 4.13 of the Standard EN 14325: 2018 Class 1 < 10% Class 2 < 5% Class 3 < 1%	Sulphuric Acid 30% Sodium Hydroxide 10% O-Xylene 1-butanol Achieved	2020TM0206
Resistance to penetration of contaminated liquids under hydrostatic pressure	4.1.4.1	Class 1 0 < kPa < 1,75 Class 2 1,75 < kPa < 3,5 Class 3 3,5 < kPa < 7 Class 4 7 < kPa < 14 Class 5 14 < kPa < 20 Class 6 > 20 kPa	Achieved Class 6	2020TM0206

—————>>>



EVALUATION

2.2.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 14126:2003/AC:2004

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Resistance to the penetration of biological agents by mechanical contact with substances containing contaminated liquids	4.1.4.2	Class 1 $t \leq 15$ min Class 2 $15 < t \leq 30$ Class 3 $30 < t \leq 45$ Class 4 $45 < t \leq 60$ Class 5 $60 < t \leq 75$ Class 6 $t > 75$ min	Achieved Class 1	2020TM0206
Penetration resistance of contaminated liquid aerosols	4.1.4.3	Class 1 $1 < \log \leq 3$ Class 2 $3 < \log \leq 5$ Class 3 $\log > 5$	No tested	---
Penetration resistance of contaminated solid particles	4.1.4.4	Class 1 $2 < \log ufc \leq 3$ Class 2 $1 < \log ufc \leq 2$ Class 3 ≤ 1	Achieved Class 3	2020TM0206

>>>



EVALUATION

2.2.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 14126:2003/AC:2004

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Seam strength	4.2	According to the point 5.5 of the Standard EN 14325: 2018 Class 1 $30 < N < 50$ Class 2 $50 < N < 75$ Class 3 $75 < N < 125$ Class 4 $125 < N < 300$ Class 5 $300 < N < 500$ Class 6 $> 500 N$	Achieved Class 1	2020TM0206
Determination of resistance to liquid penetration by spray	4.3	Shall not produce penetration	Achieved	2020TM0206
Inward leakage of aerosols of fine particles into suits	4.3	$IL_{82/90} \leq 30\%$ and $TILS_{8/10} \leq 15\%$	Achieved	2020TM0206

—————>>>



EVALUATION

2.3.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 13034:2005 + A1:2009

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Design	5.1	The garment fulfills design requirement of the Standard EN 340	Achieved	2020TM0206
Resistance to abrasión	4.1	According to the point 4.4 of the Standard EN 14325: 2004 Level 1 > 10 cycles Level 2 > 100 cycles Level 3 > 500 cycles Level 4 > 1000 cycles Level 5 > 1500 cycles Level 6 > 2000 cycles	Achieved Level 1	2020TM0206
Determination of tear resistance	4.1	According to the point 4.7 of the Standard EN 14325: 2004 Level 1 > 10 N Level 2 > 20 N Level 3 > 40 N Level 4 > 60 N Level 5 > 100 N Level 6 > 150 N	Achieved Level 1	2020TM1850

—————>>>



EVALUATION

2.3.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 13034:2005 + A1:2009

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Tensile	4.1	According to the point 4.9 of the Standard EN 14325: 2004 Nivel / Level 1 > 30 ciclos / cycles Nivel / Level 2 > 60 ciclos / cycles Nivel / Level 3 > 100 ciclos / cycles Nivel / Level 4 > 250 ciclos / cycles Nivel / Level 5 > 500 ciclos / cycles Nivel / Level 6 > 1000 ciclos / cycles	Achieved Level 2	2020TM0206
Puncture resistance	4.1	According to the point 4.10 of the Standard EN 14325: 2004 Class 1 5 < N < 10 Class 2 10 < N < 50 Class 3 50 < N < 100 Class 4 100 < N < 150 Class 5 150 < N < 250 Class 6 > 250 N	Achieved Level 1	2020TM1850

----->>>



EVALUATION

2.3.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN 13034:2005 + A1:2009

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Repellency to liquids	4.1	According to the point 4.12 of the Standard EN 14325: 2004 Level 3 > 95%	Sulphuric Acid 30% Sodium Hydroxide 10% O-Xylene 1-butanol Achieved	2020TM0206
Resistance to penetration to liquids	4.1	According to the point 4.13 of the Standard EN 14325: 2004 Level 3 < 1%	Sulphuric Acid 30% Sodium Hydroxide 10% O-Xylene 1-butanol Achieved	2020TM0206
Determination of resistance to liquid penetration by spray	5.2	Shall not produce penetration	Achieved	2020TM0206
Seam strength	4.2.2	According to the point 5.5 of the Standard EN 14325: 2004 Level 1 > 30 cycles Level 2 > 50 cycles Level 3 > 75 cycles Level 4 > 125 cycles Level 5 > 300 cycles Level 6 > 500 cycles	Achieved Level 1	2020TM0206

→→→



EVALUATION

2.4.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN ISO 13982-1:2004/A1:2010

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Design	4.3.1	La prenda cumple con la exigencia de diseño. The garment fulfills design requirement	Achieved	2020TM0206
Dimensional stability after 5 washing cycles 60°C	4.3.1	Changes of dimension due to cleaning shall not exceed 3% for woven materials and 5% for knitted material and nonwovens.	Not applicable	---
pH determination	4.3.1	Entre 3,5 y 9,5 Between 3,5 and 9,5	Achieved	19.0.84437
Determination of forbidden azoic colorants	4.3.1	None detected	Not applicable	---
Resistencia to abrasión	4.1	According to the point 4.4 of the Standard EN 14325: 2004 Class 1 10 < cycles < 100 Class 2 100 < cycles < 500 Class 3 500 < cycles < 1000 Class 4 1000 < cycles < 1500 Class 5 1500 < cycles < 2000 Class 6 > 2000 cycles	Achieved Class 1	2020TM0206

→→→



EVALUATION

2.4.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN ISO 13982-1:2004/A1:2010

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Compression-folding flex cracking	4.1	According to the point 4.5 of the Standard EN 14325: 2004 Class 1 1000 < cycles < 2500 Class 2 2500 < cycles < 5000 Class 3 5000 < cycles < 15000 Class 4 15000 < cycles < 40000 Class 5 40000 < cycles < 100000 Class 6 > 100000 cycles	Achieved Class 6	2020TM0206
Determination of tear resistance	4.1	According to the point 4.7 of the Standard EN 14325: 2004 Class 1 10 < N < 20 Class 2 20 < N < 40 Class 3 40 < N < 60 Class 4 60 < N < 100 Class 5 100 < N < 150 Class 6 > 150 N	Achieved Class 1	2020TM1850

—————>>>



EVALUATION

2.4.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN ISO 13982-1:2004/A1:2010

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Puncture resistance	4.1	According to the point 4.10 of the Standard EN 14325: 2004 Class 1 $5 < N < 10$ Class 2 $10 < N < 50$ Class 3 $50 < N < 100$ Class 4 $100 < N < 150$ Class 5 $150 < N < 250$ Class 6 $> 250 N$	Achieved Class 1	2020TM1850
Resistance to ignition	4.1	According to the point 4.14 of the Standard EN 14325:2004 material shall not form droplets and it shall not continue to burn for more than 5 s after removal from the flame	Not Achieved	2020TM0206

→→→



EVALUATION

2.4.-APPLICABLE REQUIREMENTS ACCORDING TO THE STANDARD EN ISO 13982-1:2004/A1:2010

TEST	CLAUSE	REQUIREMENT	RESULTS	REPORT No.
Seam strength	4.2.2	According to the point 5.5 of the Standard EN 14325: 2004 Class 1 $30 < N < 50$ Class 2 $50 < N < 75$ Class 3 $75 < N < 125$ Class 4 $125 < N < 300$ Class 5 $300 < N < 500$ Class 6 $> 500 N$	Achieved Class 1	2020TM0206
Inward leakage of aerosols of fine particles into suits	4.3.2	$IL_{82/90} \leq 30\%$ and $TILS_{8/10} \leq 15\%$	Achieved	2020TM0206

///



CONCLUSION OF THE CONFORMITY EVALUATION

AITEX, Notified Body N° 0161, concludes that:

The PPE DZ COVERALL, complies with all essential Requirements as regards health and safety in compliance with the indications in the Regulation (EU) 2016/425 in compliance with harmonised standards EN ISO 13688:2013: "Protective Clothing – General Requirements" EN 13034: 2005+A1: 2009" chemical protective clothing (TYPE [6])" Hydroxide sodium (10%), sulphuric acid (30%), O-Xylene and 1-Butanol, EN ISO13982-1:2004/A1:2010 "for the protection against risks of penetration of solid particles suspended in the air as a complete path". (TYPE 5) and EN 14126:2003/AC:2004 for protection against biological agents (TYPE 5, 6-B)

The CAT. III PPE shall only be used in conjunction with one of the conformity assessment procedures according to Module C2 or Module D described in Article 19 letter c) of the Regulation (EU) 2016/425.

—————>>>



Lucia Martinez

Head of PPE and Ballistics department

LIABILITY CLAUSES

- 1.- AITEX is liable only for the results of the methods of analysis used, as expressed in the report and referring exclusively to the materials or samples indicated in the same which are in its possession, the professional and legal liability of the Centre being limited to these. Unless otherwise stated, the samples were freely chosen and sent by the applicant.
- 2.- AITEX shall not be liable in any case of misuse of the test materials nor for undue interpretation or use of this document
- 3.- The Offer and / or Order to which the applicant gives approval through signature and seal, constitutes the Legally Executable Agreement in which AITEX is responsible for safeguarding and guaranteeing the absolute confidentiality of the management of all the information obtained or created during the performance of the contracted activities.
- 4.- In the eventuality of discrepancies between reports, a check to settle the same will be carried out in the head offices of AITEX. Also, the applicants undertake to notify AITEX of any complaint received by them as a result of the report, exempting this Centre from all liability if such is not done, the periods of conservation of the samples being taken into account.
- 5.- AITEX is not responsible for the information provided by customers, which is reflected in the Report, and may affect the validity of the results.
- 6.- AITEX will provide at the request of the person concerned, the treatment of complaints procedure.
- 7.- AITEX is not responsible for an inadequate state of the sample received that could compromise the validity of the results, expressing such circumstance, in the test reports.
- 8.- AITEX may include in its reports, analyses, results, etc., any other evaluation which it considers necessary, even when it has not been specifically requested.
- 9.- When a Declaration of Conformity is requested, if not indicated otherwise, the decision rule will be applied according to ILAC-G8 & ISO 10576-1, in case of ambiguity, or indeterminacy
- 10.- The uncertainties of tests, which are made explicit in the Results Report, have been estimated for a $k = 2$ (95% probability of coverage). If not informed, they are available to the client in AITEX.
- 11.- The original materials and rests of samples, not subject to test, will be retained in AITEX during the twelve months following the issuance of the report, so that any check or claim which, in his case, wanted to make the applicant, should be exercised within the period indicated.
- 12.- This report may only be sent or delivered by hand to the applicant or to a person duly authorised by the same.
- 13.- The results of the tests and the statement of compliance with the specification in this report refer only to the test sample as it has been analyzed / tested and not the sample / item which has taken the test sample.
- 14.- The client must attend at all times, to the dates of the realization of the tests.
- 15.- According to Resolution EA (33) 31, the test reports must include the unique identification of the sample, and any brand or label of the manufacturer may be added. It is not allowed to re-issue test reports of untested sample names (references), they can only be re-issued for error correction or inclusion of omitted data that were already available at the time of the test. The laboratory can not assume responsibility for declaring that the product with the new trade name / trademark is strictly identical to the one originally tested; This responsibility belongs to the client.